

# WH-1200 Outdoor CCTV camera

## Outdoor day/night surveillance camera

The WH-1200 Outdoor CCTV camera is color CCD sensor, best for outdoor surveillance, with 20M IR LEDs sensor, which can be application in day/night video surveillance situation, even under low light or no light condition, capture clear image and more detail.

The WH-1200 outdoor CCTV camera is high performance surveillance camera, combines powerful video-processing chip and IP66 standard ensures the camera is protected from water and dust outdoors to meet your harsh environments surveillance solution.




### Highlights

- ▶ IP66 waterproof for outdoor surveillance
- ▶ High resolution 420TV lines
- ▶ Standard 6.0mm Lens
- ▶ Advanced 1/3 Super HAD CCD Sensor
- ▶ Infrared LEDs for night vision surveillance
- ▶ High Sensitivity of 0.1Lux
- ▶ Advanced digital signal processor (DSP)
- ▶ Wide range Operating temperature range
- ▶ Ideal for low light surveillance application

### Powerful Video-Processing chip

- Outstanding image quality
- Exceptional dynamic range
- Captures more detail



### Enhancement of camera performance

- Green design
- 100% passed durability test
- Innovated and practical design
- Temperature test, voltage protective test

### Reliability Test

- Color Testing
- Vector Testing
- Frequency Testing
- Video Quality Testing



<b>Model</b>	<b>WH-1200</b>
<b>Image Sensor</b>	1/3" Color Super HAD CCD
<b>Picture Elements</b>	NTSC: 542 x 492 PAL: 542 x 582
<b>Scanning system</b>	NTSC: 525 lines, PAL: 625 lines. 2:1 interlace
<b>Lens</b>	6.0mm lens
<b>H-Resolution</b>	420 TV lines
<b>Min illumination</b>	0.1Lux/ F1.2
<b>S/N ratio</b>	More than 48 dB
<b>Electronic Shutter</b>	NTSC: 1/60 ~ 1/100,000 PAL: 1/50 ~ 1/110,000
<b>Back light Comp.</b>	Auto
<b>White Balance</b>	Auto
<b>Infrared LEDs (Night Vision)</b>	Yes
<b>Video Output</b>	1.0Vp-p, 75 Ohm, BNC connector
<b>Power</b>	
<b>Power</b>	DC12V/500mA
<b>Power consumption</b>	3.2W
<b>Operating environment</b>	
<b>IP66 Outdoor waterproof</b>	Yes
<b>Operating Temperature</b>	-10 °C ~ 50 °C
<b>Storage Temperature</b>	-10 °C ~ 50 °C
<b>Humidity</b>	RH 85%
<b>Dimensions</b>	120mm x 74.5mm
<b>EMI</b>	
CE, UL	



**World Helmsman Technology Co., Ltd.**

3F-5, No. 81, Sec. 1, Hsin Tai Wu Rd., Hsichih,

Taipei Hsien 22101, Taiwan

Tel: +886-2-2906-0816 Fax: +886-2-2904-1360

[www.wh-tech.com](http://www.wh-tech.com) / Email: [sales@wh-tech.com](mailto:sales@wh-tech.com)

■ DISTRIBUTED BY

