WH-2400 fixed dome CCTV camera

Color CCD surveillance camera

The WH-2400 fixed dome CCTV camera is color CCD camera, deliver high quality image, ideal for indoor video surveillance applications.

The fixed dome security camera use 1/3” color CCD sensor and built-in 3.6mm lens, produces best quality image, to meet you standard light condition security surveillance applications, such as home, office, and school.

The dome security camera with minimum light of 0.3 Lux and advanced digital signal processor, which can be capture more detail and color reproductions.

Highlights

- High resolution 380 TV lines surveillance camera
- With 3.6mm wide angle lens
- Advanced 1/3 Super HAD CCD Sensor
- High Sensitivity of 0.3Lux
- Advanced digital signal processor (DSP)
- -10°C ~ +50°C Operating temperature range
- Ideal for indoor surveillance application

Powerful Video-Processing chip

- Outstanding image quality
- Exceptional dynamic range
- Captures more detail



Reliability Test

- Color Testing
- Vector Testing
- Frequency Testing
- Video Quality Testing

Enhancement of camera performance

- Green design
- 100% passed durability test
- Innovated and practical design
- Temperature test, voltage protective test

Model	WH-2400
Image Sensor	1/3” Color Super HAD CCD
Picture Elements	NTSC: 542 x 492 PAL: 542 x 582
Scanning system	NTSC: 525 lines, PAL: 625 lines. 2:1 interlace
Lens	Standard 3.6mm Lens
Iris Control	NO
H-Resolution	380 TV lines
Min illumination	0.3Lux/ F1.2
S/N ratio	More than 48 dB
Electronic Shutter	NTSC: 1/60 ~ 1/100,000 PAL: 1/50 ~ 1/110,000
Back light Comp.	Auto
White Balance	Auto
Day/Night	NO
Video Output	1.0Vp-p, 75 Ohm, BNC connector
Power	
Power	DC12V/300mA
Power consumption	3.2W
Operating environment	
Operating Temperature	-10 °C ~ 50 °C
Storage Temperature	-10 °C ~ 50 °C
Humidity	RH 95%
EMI	
CE, UL	

World Helmsman Technology Co., Ltd.
3F-5, No. 81, Sec. 1, Hsin Tai Wu Rd., Hsichih,
Taipei Hsien 22101, Taiwan
Tel: +886-2-2906-0816 Fax: +886-2-2904-1360
www.wh-tech.com / Email: sales@wh-tech.com

■ DISTRIBUTED BY